1000 BTUH 48 VOLT DC POWERED AIR CONDITIONER INDOOR/OUTDOOR, UL TYPES 12, 4 & 4X AVAILABLE

Engineered & manufactured to endure the most difficult of environments and applications. Thermal Edge air conditioners will exceed environmental requirements in applications like Telecom Outside Plant, Off-Grid Solar, Wind & other Battery Powered Electrical Cabinets. The CS011 uses a unique 3 coil design providing high capacity cooling while utilizing air intake from either side. Dual intake allows for mounting on a wall mounted enclosure on the right or left side of your enclosure.



• Custom Finish

• Extended Temp. Probe

Remote Control/Monitor

OPTIONS:

- High Ambient
- Remote Controller
- Corrosion Protection
- Dry Contact
- Controller Programming
- Open Door Kill Switch

Digital Temperature Controller

- Programmable set point and temperature controls
- Visible Error and/or alarm messaging
- System status indication & keypad lockout function

Active Condensate Evaporation System

- · Constant elimination of condensate
- Increases unit efficiency by pre-cooling refrigerant

Key Design Features

- Designed with rigid chassis and seam welded shroud
- Thoughtful interior design for easy maintenance
- Narrow body style fits on 8" enclosure
- Filter free design


Unit Efficiency


- Highly efficient rotary compressor
- Fully insulated & sealed cabinet
- Thermal Expansion Valve to maintain cooling capacity over a broad ambient temperature range

Compressor Protection System

- High & Low refrigerant cutouts with fault indication
- Compressor anti short cycle protection
- Thermal overload protector
- Compressor motor drive controller eliminates power inrush, saves energy and increases compressor life

| Model | UL Type | BTU/Hour | Material | Voltage | Running Amps | Max. Amb. Temp. | HxWxD | Unit Weight (lbs.) |
|--------------|------------|----------|----------------------|---------|-----------------|--------------------|---------------|-----------------------|
| C\$011D4812 | 12 | 1000 | Powder coated steel | 48 VDC | 3.5 | 131°F | 17" x 7" x 7" | 31 |
| CS011D4804 | 4 | 1000 | Powder coated steel | 48 VDC | 3.5 | 131°F | 17" x 7" x 7" | 31 |
| CS011D484X | 4X | 1000 | Stainless steel | 48 VDC | 3.5 | 131°F | 17" x 7" x 7" | 31 |
| CS011D484XL6 | 4X | 1000 | Mill finish aluminum | 48 VDC | 3.5 | 131°F | 17" x 7" x 7" | 23 |





ATTENTION: If ordering a replacement for a Thermal Edge air conditioner, please include the part number and serial number of the unit being replaced in your order. This will ensure that we ship a replacement that is compatible with the cutout dimensions and power connection features of the older model. All information subject to change without notice.

