

**6000 BTUH 230V**
**INDOOR/OUTDOOR, UL TYPES 12, 4 & 4X AVAILABLE**

Engineered & manufactured to endure the most difficult of environments and applications. Thermal Edge air conditioners will exceed environmental requirements in applications like Steel, Food Processing, Petro-Chemical, Cement, Paper & Pulp and Plastics.



## Digital Temperature Controller

- Programmable set point and temperature controls
- Visible Error and/or alarm messaging
- System status indication & keypad lockout function

## Active Condensate Evaporation System

- Constant elimination of condensate
- Increases unit efficiency by pre-cooling refrigerant

## Key Design Features

- Sloped top to allow for water runoff
- Designed with rigid chassis and seam welded shroud
- Thoughtful interior design for easy maintenance
- Narrow body style fits on 12" enclosure

## Unit Efficiency

- Temperature operated condenser fan reduces power inrush and saves energy
- Highly efficient rotary compressor
- Fully insulated & sealed cabinet
- Thermal Expansion Valve to maintain cooling capacity over a broad ambient temperature range

## Compressor Protection System




- High & Low refrigerant cutouts with fault indication
- Compressor anti short cycle protection
- Thermal overload protector
- Compressor run capacitors reduce power inrush, save energy and increase compressor life

## OPTIONS:

- Low and High Ambient
- Remote Controller
- Corrosion Protection
- Dry Contact
- Redundant System
- Filter/Filter Frame
- Controller Programming
- Heater
- Hazardous Location
- Open Door Kill Switch
- Custom Finish
- Extended Temperature Probe
- Remote Control/Monitor
- Vibration Resistant
- Diagnostics

Model	UL Type	BTU/Hour	Material	Voltage/Phase/Hz.	Running Amps	Max. Amb. Temp.	H x W x D	Weight (lbs.) Unit/Ship
NE06023712	12	6000	Powder coated steel	230/1/50 230/1/60	3.7 4.2	131°F	44.36" x 11.8" x 15"	170 / 195
NE06023704	4	6000	Powder coated steel	230/1/50 230/1/60	3.7 4.2	131°F	44.36" x 11.8" x 15"	170 / 195
NE0602374X	4X	6000	Stainless steel	230/1/5 230/1/60	3.7 4.2	131°F	44.36" x 11.8" x 15"	170 / 195
NE0602374XL4	4X	6000	Mill finish aluminum	230/1/50 230/1/60	3.7 4.2	131°F	44.36" x 11.8" x 15"	160 / 185

Testing done under controlled conditions. Actual performance may vary.



UL File # SA32252



**ATTENTION:** If ordering a replacement for a Thermal Edge air conditioner, please include the part number and serial number of the unit being replaced in your order. This will ensure that we ship a replacement that is compatible with the cutout dimensions and power connection features of the older model. All information subject to change without notice.