

50 HZ AIR CONDITIONER PRODUCT LINE

Model	BTU/Hour	Voltage/ Phase/Hz	Running Amps	Max. Ambient Temp	Max. Integrated Heat (Watts)	H x W x D	Unit Weight
CS011105	1,000	100/1/50	2.7	125°F	350	17" x 7" x 7"	31
NE010105	1,000	100/1/50	2.3	125°F	NA	22" x 11.8" x 8.5"	53
NE010205	1,000	200/1/50	1.9	125°F	NA	22" x 11.8" x 8.5"	53
NE015105	1,500	100/1/50	2.4	125°F	NA	22" x 11.8" x 8.5"	53
NE015205	1,500	200/1/50	1.9	125°F	NA	22" x 11.8" x 8.5"	53
CS020235	2,000	230/1/50	1.7	131°F	500	20" x 10" x 10"	49
NE020105	2,000	100/1/50	5.2	125°F	1000	32" x 11.8" x 9.5"	65
NE020235	2,000	230/1/50	1.7	125°F	1000	32" x 11.8" x 9.5"	65
NE020385	2,000	380/1/50	1.4	125°F	1000	32" x 11.8" x 9.5"	99
NE020405	2,000	400/1/50	1.3	125°F	1000	38" x 11.8" x 9.5"	99
NE020415	2,000	415/1/50	1.25	125°F	1000	38" x 11.8" x 9.5"	99
NE030105	3,000	100/1/50	5.0	125°F	1000	38" x 11.8" x 9.5"	66
NE030205	3,000	200/1/50	3.07	125°F	1000	38" x 11.8" x 9.5"	99
NE030385	3,000	380/1/50	1.32	125°F	1000	38" x 11.8" x 9.5"	99
NE030405	3,000	400/1/50	1.28	125°F	1000	38" x 11.8" x 9.5"	99
NE030415	3,000	415/1/50	1.2	125°F	1000	38" x 11.8" x 9.5"	99
NE050237	5,000	230/1/50-60	4.0/3.1	131°F	1000	44.63" x 11.8" x 15.1"	170
NE050235	5,000	230/1/50	3.4	131°F	1000	36" x 11.8" x 15.1"	92
NE050385	5,000	380/1/50	2.1	131°F	1000	44.63" x 11.8" x 15.1"	136
NE050405	5,000	400/1/50	1.9	131°F	1000	44.63" x 11.8" x 15.1"	136
NE050415	5,000	415/1/50	1.9	131°F	1000	44.63" x 11.8" x 15.1"	136

50 HZ AIR CONDITIONER PRODUCT LINE

(CONTINUED)

Model	BTU/Hour	Voltage/ Phase/Hz	Running Amps	Max. Ambient Temp	Max. Integrated Heat (Watts)	H x W x D	Unit Weight
NE060237	6,000	230/1/50-60	4.2/3.7	131°F	1000	44.63" x 11.8" x 15.1"	170
NE060235	6,000	230/1/50	4.0	131°F	1000	36" x 11.8" x 15.1"	98
NE060385	6,000	380/1/50	2.4	131°F	1000	44.63" x 11.8" x 15.1"	142
NE060405	6,000	400/1/50	2.3	131°F	1000	44.63" x 11.8" x 15.1"	142
NE060415	6,000	415/1/50	2.2	131°F	1000	44.63" x 11.8" x 15.1"	142
HC080235	8,000	230/1/50	7.1	125°F	1000	48" x 15.9" x 15.1"	166
HC080385	8,000	380/1/50	4.3	125°F	1000	57.6" x 15.9" x 15.1"	232
HC080405	8,000	400/1/50	4.1	125°F	1000	57.6" x 15.9" x 15.1"	232
HC080415	8,000	415/1/50	3.8	125°F	1000	57.6" x 15.9" x 15.1"	232
HC101235	10,000	230/1/50	6.4	131°F	1500	48" x 15.9" x 15.1"	166
HC101385	10,000	380/1/50	3.9	131°F	1500	57.6" x 15.9" x 15.1"	232
HC101405	10,000	400/1/50	3.7	131°F	1500	57.6" x 15.9" x 15.1"	232
HC101415	10,000	415/1/50	3.6	131°F	1500	57.6" x 15.9" x 15.1"	232
HC121235	12,000	230/1/50	8.6	131°F	1500	48" x 15.9" x 15.1"	163
HC121385	12,000	380/1/50	5.2	131°F	1500	57.6" x 15.9" x 15.1"	237
HC121405	12,000	400/1/50	4.9	131°F	1500	57.6" x 15.9" x 15.1"	237
HC121415	12,000	415/1/50	4.8	131°F	1500	57.6" x 15.9" x 15.1"	237